

WARNING Avoid contact with eyes and skin. Do NOT ingest. ONLY for use in engine fuel systems. KEEP OUT OF REACH OF CHILDREN. Comes with childproof screw cap.

STORAGE DO NOT store in direct sunlight or at high temperatures.

EffiTab International AB

Folke Bernadottes väg 445 256 57 Ramlösa E-post: office@effitab.com



www.effitab.com

User Manual - liquid

First refuelling:

- 1. Check how much the tank holds in total in terms of number of litres.
- 2. Fill the tank with fluid for the total volume of the tank according to the table below (Tank No. 1-2).
- 3. Fill up with a full tank. (*This is so that the whole first tank will have the right concentration.*)

Second refuelling:

- 1. Refuel and check how many litres have been filled.
- 2. Top up with liquid according to the table below (Tank No. 1-2).

Third refueling and onwards:

- 1. Refuel and check how many litres have been filled.
- 2. Top up with fluid according to the table below (Tank No. 3 onwards).

NB!

In case of the slightest uncertainty in dosage, please contact EffiTab.

For larger volumes, a personal contact with EffiTab is recommended for review and instructions.

| Product | Tank No. 1-2 | Tank No. 3 |
|------------------------------------|-----------------|------------|
| EffiTab Gold Fuel Treatment | 1/3000 | 1/4000 |
| EffiTab Gold Fuel Treatment HFO/ | 1/4000 | 1/5000 |
| | Temperature | Ratio |
| EffiTab Gold Fuel Treatment ARCTIC | -10 °C – -15 °C | 1:4000 |
| | -15 °C – -20 °C | 1:3000 |
| | -20 °C – -25 °C | 1:2500 |
| | -25 °C – -30 °C | 1:2000 |
| | -30 °C – -35 °C | 1:1500 |
| | -40 °C -> | 1:500 |